

## Universalkleber

11294-0008

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Universalkleber

Article number: 5008-0001

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Adhesive for use in the field of dental technology

Holders / adhesive for wax parts

#### 1.3. Details of the supplier of the safety data sheet

Company name: YETI Dentalprodukte GmbH

Street: Industriestrasse 3

Place: D-78234 Engen

Telephone: +49 7733-9410-0

Telefax: +49 7733-9410-22

Responsible Department: sdb@yeti-dental.com

Responsible for the safety data sheet: sds@gbk-ingelheim.de

#### 1.4. Emergency telephone

+49 7733-9410-0 (Mo-Do 8:00 - 16:30, Fr 8:00 - 15:00)

#### number:

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

#### 2.2. Label elements

##### Regulation (EC) No. 1272/2008

##### Hazard components for labelling

methyl acetate

n-butyl acetate

Signal word:

Danger

Pictograms:



##### Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## Universalkleber

11294-0008

P312	Call a POISON CENTER/doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P235	Keep cool.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional advice on labelling

The product is labeled in accordance with Regulation (EC) no. 1272/2008 (GHS).

### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture containing following substances with additives

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
79-20-9	methyl acetate			40 - 75 %
	201-185-2	607-021-00-X		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			10 - 35 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			

Full text of H and EUH statements: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately. In the event of symptoms refer for medical treatment.

#### After inhalation

Ensure of fresh air. Get medical attention, if respiratory irritation develops or if breathing becomes difficult. In case of the person being unconscious put him/her in a stable side position.

#### After contact with skin

Wash off with soap and plenty of water. Consult a doctor if skin irritation persists.

#### After contact with eyes

Remove contact lens. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical treatment by eye specialist.

#### After ingestion

Rinse mouth. Do not induce vomiting. Do not give neutralising liquids. Summon a doctor immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation. Vapours may cause drowsiness and dizziness. Following inhalation/eye contact: irritation of the mucous membranes, a numbing effect, impaired reaction times and sense of coordination are possible at high concentrations. Headache, dizziness, nausea, etc. may arise following prolonged inhalation of high vapour concentrations.

### 4.3. Indication of any immediate medical attention and special treatment needed

In case of the person being unconscious summon a doctor immediately.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

## Universalkleber

11294-0008

---

### Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

### Unsuitable extinguishing media

Full water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire may produce: Carbon monoxide and carbon dioxide. Vapours are heavier than air and spread along ground.

Flashback at a long distance is possible.

### 5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

### Additional information

Vapours are heavier than air and spread along ground. The vapour/air mixture is explosive, even in empty, uncleaned receptacles. Risk of bursting of the receptacle. Cool containers at risk with water spray jet. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator. Ensure adequate ventilation. Use personal protective clothing. Keep away sources of ignition. Single out leaking and leaky spray cans, empty and dispose them according to regulations. Avoid contact with skin, eyes and clothing. Do not breathe vapours. Do not breathe spray.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

For limiting emissions from volatile, organic compounds (VOC) solvent vapours are to be fed into a waste gas purification facility.

### 6.3. Methods and material for containment and cleaning up

Pump off larger quantity.

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal. Take measures against electrostatic charging. Use only non-sparking tools.

Clean contaminated surface thoroughly.

### 6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Do not keep containers unlocked. Handle in accordance with the general hygienic rules. When using do not eat, drink or smoke. Wash hands before breaks and at the end of workday. Take off contaminated clothing and wash it before reuse.

#### Advice on protection against fire and explosion

Do not smoke - volatile. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Use only explosion-proof equipment. Vapours are heavier than air and spread along ground. Vapours can form an explosive mixture with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

#### Advice on storage compatibility

Incompatible with oxidizing agents.

#### Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

### 7.3. Specific end use(s)

Adhesive for use in the field of dental technology

Holders / adhesive for wax parts

---

## SECTION 8: Exposure controls/personal protection

# Universalkleber

11294-0008

## 8.1. Control parameters

### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
79-20-9	Methyl acetate	200	616		TWA (8 h)	WEL
		250	770		STEL (15 min)	WEL

## 8.2. Exposure controls

### Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

### Protective and hygiene measures

Do not inhale vapours. Avoid contact with eyes and skin. Wash hands before breaks and immediately after handling the product. When using do not eat, drink or smoke. Take off immediately all contaminated clothing.

### Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

### Hand protection

Protective gloves resistant to chemicals made off viton , minimum coat thickness 0,7 mm, permeation resistance (wear duration) approx. 10 minutes, i.e. protective glove <Vitoject 890> made by www.kcl.de. Chemical safety gloves made of butyl or nitrile rubber of category III according to EN 374.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

### Skin protection

Long sleeved clothing (EN 368).

### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	Colourless - yellowish	
Odour:	Ethereal	
pH-Value:	Not applicable	DIN 19268

### Changes in the physical state

Melting point:	Not determined	
Initial boiling point and boiling range:	(697 hPa) 56 °C	
Sublimation point:	Not determined	
Softening point:	Not determined	
Pour point:	Not determined	
Flash point:	-13 °C	DIN 51755
Sustaining combustion:	No data available	
Flammability		Not determined
Explosive properties	The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated. Heating will cause pressure rise with risk of bursting.	
Lower explosion limits:	3,1 vol. %	
Upper explosion limits:	16 vol. %	
Ignition temperature:	455 °C	DIN 51704
Auto-ignition temperature		Not determined
Decomposition temperature:	Not applicable	
Oxidizing properties	Not determined	

## Universalkleber

11294-0008

Vapour pressure: (at 20 °C)	2470 hPa	
Density (at 20 °C):	0,96 g/cm <sup>3</sup>	ISO 2811-1
Water solubility: (at 20 °C)	Miscible	
Partition coefficient:	Not determined	
Viscosity / dynamic:	Not determined	
Viscosity / kinematic:	Not determined	
Flow time: (at 20 °C)	20 s	DIN 53211/4
Vapour density:	Not determined	

### 9.2. Other information

No data available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No decomposition if stored and applied as directed. Protect from heat/ overheating. Risk of explosion.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Evolution of highly flammable gases/vapours.

### 10.4. Conditions to avoid

Vapours may form explosive mixture with air. (9°C)

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

### 10.5. Incompatible materials

Oxidizing agents (strong).

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
123-86-4	n-butyl acetate				
	oral	LD50	10800 mg/kg	Rat	
	dermal	LD50 mg/kg	> 17600	Rabbit	

#### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause drowsiness or dizziness. (methyl acetate), (n-butyl acetate)

#### Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### Practical experience

## Universalkleber

11294-0008

### Other observations

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecological data are not available.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	18 - 185 mg/l	96 h		REACH / GESTIS

### 12.2. Persistence and degradability

All organic substances contained in the product correspond with the criteria of the test OECD 302 B and the values required for complete biodegradability in Regulation (EC) 648/2004 on Detergents.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

### 12.6. Other adverse effects

Low hazard to waters.

### Further information

Do not flush into surface water or sanitary sewer system.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Advice on disposal

This material and its container must be disposed of as hazardous waste. Where possible recycling is preferred to disposal.

The waste code number must be agreed with the disposer / manufacturer / competent authority.

#### Waste disposal number of waste from residues/unused products

080411 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); adhesive and sealant sludges containing organic solvents or other hazardous substances  
Classified as hazardous waste.

#### Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances  
Classified as hazardous waste.

#### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Contaminated packagings are to be treated like the product itself.

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III

# Universalkleber

11294-0008

Hazard label: 3



Classification code: F1  
 Special Provisions: 640E  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 Transport category: 3  
 Hazard No: 30  
 Tunnel restriction code: D/E

## Inland waterways transport (ADN)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Classification code: F1  
 Special Provisions: 640E  
 Limited quantity: 5 L  
 Excepted quantity: E1

## Marine transport (IMDG)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: 223, 955  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-E, S-D

## Air transport (ICAO)

**14.1. UN number:** UN 1133  
**14.2. UN proper shipping name:** Adhesives  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
 Hazard label: 3



Special Provisions: A3  
 Limited quantity Passenger: 10 L  
 Passenger LQ: Y344  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 355  
 IATA-max. quantity - Passenger: 60 L  
 IATA-packing instructions - Cargo: 366  
 IATA-max. quantity - Cargo: 220 L

## Universalkleber

11294-0008

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

---

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

2004/42/EC (VOC): > 90 %

#### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

---

## SECTION 16: Other information

### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

### Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)



**Safety Data Sheet** according to Regulation (EC) No 1907/2006

YETI Dentalprodukte GmbH

Revision date: 09.05.2016

Revision No: 1,1

## **Universalkleber**

11294-0008

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*